



Triple Glazing Performance
in a standard 28mm profile

TRIPLE
LYTE

This is TripleLyte - Minimal in Size. Maximum in Performance.

Triple glazing has always meant a thicker, heavier unit. Too bulky for most existing frames. Too much disruption for a straightforward replacement job.

TripleLyte from Whiteline changes that.

Full triple-glazing performance inside a standard 28mm double-glazing profile that fits straight into existing beads and gasket systems.

At just 22.75kg per square metre, it's dramatically lighter than standard triple glazing, and with a centre-pane U-value from 0.8 to 1.1 W/m²K*, depending on glass specification, this is the upgrade you're looking for.

ULTRA-SLIM AND FITTER FRIENDLY Triple glazing technology in a 28mm unit

Most triple glazing is bulky, but with TripleLyte, it's only 15% heavier than double glazing, fits easily into existing 28mm frames, and it's lightweight removes stress from hardware.

LOWER ENERGY BILLS Lowest U-value and Low-Emissivity

Improves insulation and reduces heat loss, delivering exceptional thermal efficiency ratings and lowering winter energy bills.

SAFE AND SOUND Monolithic Glass Core™

The only triple glazed unit with 100% glass monolithic core for improved thermal efficiency, noise reduction and security.

G-value:	0.35
Centre Pane U-value:	0.8
UV reduction (standard):	90%
UV reduction (laminated):	99%

PREVENTS CONDENSATION Double Desiccant™ Technology

Latest technology absorbs trapped moisture in the spacer bars to prevent condensation.

BLOCK UV EXPOSURE Laminate Coating

A subtle green solar-control coating on the outer panes reduces UV exposure, helping protect furniture and flooring from fading.

LESS BREAK DOWNS Single Seal™ Technology

A single seal between the outer units, lowers the risk of the IGU breaking down.

